FEED ME.™

PTO/3PT ATTACHMENTS

CH5540



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

CRARY BEAR CAT®

BEARCATPRODUCTS.COM | 888.625.4520



3 year Consumer Warranty | 1 year Commercial Warranty | 6 month Rental Warranty

*U.S. & Canada Only

CH5540 CE

FEED ME.™

PTO/3PT ATTACHMENTS

- Recommend PTO Input 25 – 45 HP
- 20" x 1.25", 140 lbs.
- 4 Reversible Chipping Blades
- 5" Chipping Capacity
- Gravity/Self Feed System

IDEAL FOR:

- Ag/Orchard/ Growers
- Homeowners With Acreage
- Municipality/ Governmental Agencies
- Grounds Maintenance Crews

POWER SOURCE
- 540 RPM input
- Recommend 25 – 45 hp (19 – 34 kW) at the PTO

ROTOR ASSEMBLY
- Weighs 140 lbs. (63.50 kg)
- Machine balanced
- Rotates at 1,762 RPM
- 1.50" (3.81 cm) diameter rotor shaft
- 20" (50.80 cm) diameter by 1.25" (3.18 cm) thick
- Easily accessible through the hinged cover, when open it exposes one half of the rotor for easy access to the chipping blades and makes for easy clean out

CHIPPER BLADES
- Four reversible heat-treated steel Chipper blades
- LxWxH – 3.10" × 2" × 0.25" (7.87 cm × 5.08 cm × 0.64 cm)

ROTOR BEARINGS
- Two 1.50" (3.81 cm) greasable bearings with two bolt cast flanges

BELT DRIVE
- Double-banded belt drive
- Spring-loaded belt tensioner

ANVIL/CUTTER BAR
- Four-sided adjustable anvil to ensure good chipping ability
- 5.60" long × 4" wide × 0.38" thick (14.22 cm × 10.16 cm × 0.97 cm)

FEED CHUTE
- Feed chute opening 28" × 28" (71.12 cm × 71.12 cm)
- Tray 42.13" (107.01 cm) off the ground
- Feed throat opening is 5.57" × 6.82" (14.15 cm × 17.32 cm)
- Maximum feed size 5" (12.70 cm)

FEED SYSTEM
- Gravity-fed

INTEGRATED DISCHARGE
- With a 360° rotatable, 6" (15.24 cm) diameter steel tubing with adjustable spout cap allows you to put the chips where you want them the first time
- Discharge height is 83" (210.82 cm)

HEAVY-DUTY CONSTRUCTION
- 0.25" (0.64 cm) steel throughout housing with welded construction

MACHINE DIMENSIONS (L×W×H)
- 50" × 45" × 83" (127 cm × 114.30 cm × 210.82 cm)

WEIGHTS
- Category 1 three-point quick hitch compatible
- 600 lbs. (272.16 kg)

SAFETY
- Meets ISO safety decal standards

PARTS & ACCESSORIES

CHIPPER BLADE KIT	P/N: 72493	
PTO DOLLY KIT (SET OF 4)	P/N: 71615-00	
LOW PROFILE DISCHARGE CHUTE KIT	P/N: 71930-00	

WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

REV.01 – 03/22

UNLEASH THE POWER™

BEARCATPRODUCTS.COM | 888.625.4520