FEED ME.™

PTO/3PT ATTACHMENTS

CH9540H



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

CRARY BEAR CAT®

BEARCATPRODUCTS.COM | 888.625.4520

CH9540HXT Includes Low Profile Discharge Chute



3 year Consumer Warranty | 1 year Commercial Warranty | 6 month Rental Warranty

*U.S. & Canada Only

CH9540H

FEED ME.™

PTO/3PT ATTACHMENTS

- Recommend PTO Input 35 – 60 HP
- 30" x 1.25", 275 lbs.
- 4 Reversible Chipping Blades
- 9" Chipping Capacity
- Hydraulic Feed System
- Digital Display Control System
- Double E-Stops Standard

IDEAL FOR:

- Ag/Orchard/ Growers
- Homeowners With Acreage
- Municipality/ Governmental Agencies
- Grounds Maintenance Crews

POWER SOURCE

- 540 RPM input
- Recommend 35 – 60 hp (26 – 45 kW) at the PTO

ROTOR ASSEMBLY

- Weighs 275 lbs. (124.74 kg)
- Machine balanced
- Rotates at 1,530 RPM
- 1.75" (4.45 cm) diameter rotor shaft
- 30" (76.20 cm) diameter by 1.25" (3.18 cm) thick
- Easily accessible through the hinged cover, when open it exposes one half of the rotor for easy access to the chipping blades and makes for easy service

CHIPPER BLADES

- Four reversible heat-treated steel chipper blades
- LxWxH – 5" × 4" × 0.50" (12.70 cm × 10.16 cm × 1.27 cm)

ROTOR BEARINGS

- Two 1.75" (4.45 cm) greasable bearings with four bolt cast flanges

BELT DRIVE

- Triple-banded belt drive

ANVIL/CUTTER BAR

- Four-sided adjustable anvil to ensure good chipping ability
- 9" long × 4" wide × 0.63" thick (22.86 cm × 10.16 cm × 1.60 cm)

DIGITAL DISPLAY CONTROLLER (DDC)

- Auto feed with automatic "try again" feature
- Maximizes chipping efficiency and manpower
- Soft key menu selection buttons
- Pre-programmed maintenance schedule reminders
- Hydraulic system diagnostic capabilities
- Troubleshooting screens for in-field help
- 12V power port required

HYDRAULIC FEED SYSTEM

- Plastic hydraulic reservoir, 3 gal. (11.36 liter) capacity
- Self-contained hydraulic feed system with variable speed settings, dedicated neutral and reverse, allows you to evenly feed limbs into the chipper
- Variable feed rate with load sensing 2-stage pump
- Feed rate 0 – 120 fpm (0 – 37 m/min)
- Pump output 6.6 gpm (25 lpm) and 4 hp with maximum pressure and maximum flow, however this is rarely required
- Feed system operates under 2,500 psi
- Single 15" (38.10 cm) diameter top feed roller

FEED CHUTE

- Feed chute opening 31" × 31" (78.74 cm × 78.74 cm), tray 25" (63.50 cm) off the ground
- Feed throat opening is 9" × 9" (22.86 cm × 22.86 cm)
- 90° feed angle
- Maximum feed size up to 9" (22.86 cm)
- Electric system to control feed roller direction

INTEGRATED DISCHARGE

- **CH9540H**: 360° rotatable, 8" (20.32 cm) diameter steel tubing. Discharges from a height of 93" (236.22 cm)
- **CH9540HXT:** 360° rotatable, 6.50" × 6.50" (16.51 cm × 16.51 cm) diameter square discharge. Discharges from a height of 70.46" (178.97 cm)
- Adjustable spout cap

HEAVY-DUTY CONSTRUCTION

- 0.35" (0.97 cm) steel face plate on the rotor housing
- 0.25" (0.64 cm) steel on the rest of the housing
- Frame is 2" × 2" (5.08 cm × 5.08 cm), 7-gauge steel

MACHINE DIMENSIONS (L×W×H)

- **CH9540H**: 98" × 52" × 93" (248.92 cm × 132.08 cm × 236.22 cm)
- **CH9540HXT**: 98" × 52" × 70" (248.92 cm × 132.08 cm × 177.80 cm)

WEIGHT

- Category 1 three-point quick hitch compatible
- 1,460 lbs. (662.24 kg)

SAFETY

- Meets ISO safety decal standards

PARTS & ACCESSORIES

CHIPPER BLADE KIT	P/N: 78361-00	
PTO DOLLY KIT (SET OF 4)	P/N: 71615-00	
PTO STAND EXTENSION KIT	P/N: 71605-00	
LOW PROFILE CHUTE KIT (CH9540H)	P/N: 71725-00	
FINE CHIP ROTOR KIT	P/N: 71731-00	

WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

REV.01 – 03/22

UNLEASH THE POWER™

BEARCATPRODUCTS.COM | 888.625.4520